



FLOOR MOUNT STANDEE

A Floor Mount Standee is a durable, freestanding display system that delivers high visibility and professional presentation for promotions, branding, and information in indoor public spaces.

FEATURES

- High Visibility: Eye-level design for maximum attention.
- Stable & Durable: Strong base/frame for safe daily use.
- Easy to Move: Lightweight or wheeled for portability.
- Space-Saving: Slim vertical design occupies minimal floor space.
- Easy Content Update: Quick banner/poster change (static models).
- Static and dynamic materials, including pictures, audio, video, scrolling subtitle, PDF, web page, live video, pop-up pictures, etc.
- Multi-Use: Ideal for retail, events, lobbies, and restaurants.



Display	
Model	IIPLFS43
Screen Size (Diagonal)	43 inch
Native Resolution	1920 x 1080
Aspect Ratio	16:9
Brightness	400 cd/m ²
Contrast	1200:1
View Angle	178°(H)/178°(V)
Display Color	16.7M
Operation duration	7*24Hours
Response Time	8ms
Life Time (Light Source)	50,000 Hrs (Min.)
CPU ARM Cortex	
Memory	3GB
Storage	8GB
O/S	Android
Interface	
Interface	USB*2, RJ45*1
External Control	IR Ext (1)
Speaker	2 × 10W (8Ω)
Networks	LAN, WIFI
Touch Technology	
Touch	IR Touch
Positioning accuracy	±2mms
Transmittance	≤ 92%
Hardness	7H
Click manner	10 Points
Response Time	≤ 6ms

Power	
Power supply	AC 100~240V 50/60Hz
Power consumption	≤ 85W
Operation temperature	0°C~40°C
Operation humidity	20%~80% RH
Environment	
Operation temperature	0°C~40°C
Operation humidity	20%~80% RH
Physical	
Color	Black/White
Toughened Glass	Yes
Software	
Software	DigiSignage